

CST

**ELECTRIC 24 VOLT
COUNTERBALANCED WALKIE**
2200 / 3000 / 4000 lbs. (1000 / 1365 / 1815 kg)



STANDARD SPECIFICATIONS

10/15/20

Manufacturer's Designation		CST 10	CST 15	CST 20
Load Capacity / Rated Load @ 24" LC	lbs(kg)	2200 (1000)	3000 (1365)	4000 (1815)
Height (w/130" Two-Stage)	in(mm)	83 (2108)	83 (2108)	83 (2108)
Width	in(mm)	38 (970)	38 (970)	38 (970)
Right Angle Stack (Add Load Length and Clearance)	in(mm)	65 (1650)	65 (1650)	69.5 (1765)
Outside Turning Radius	in(mm)	58 (1475)	58 (1475)	62.5 (1588)
Travel speed loaded & unloaded	mph(kph)	2.0 (3.2) / 3.0 (4.8)	1.7 (2.8) / 3.0 (4.8)	1.6 (2.5) / 2.6 (4.2)
Power Unit		24 Volt	24 Volt	24 Volt

STANDARD FEATURES

24 volt • Key switch • Emergency power disconnect button • Fused drive and control circuits • High torque drive motor is series wound, fan cooled and has class "H" insulation for maximum protection from heat damage • Heavy duty motor contactors with replaceable tips • Ergonomic design with dual forward/reverse travel controls for thumb operation • Reversing switch at the end of the handle is spring loaded and designed to override the directional control, automatically reversing the truck on contact



For more information on this model and the full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com.